

OVERVIEW

The ADT914 Pneumatic Pressure Test Pump is a hand operated pressure pump designed to generate pressure from -14psi (-0.95bar) to 375psi (25bar). A high-quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to 10 Pa (0.1 mbar). A specially designed shut-off valve makes the pressure as stable as possible during calibration. A built-in gas-liquid isolator protects the pump from moisture and dirt to reduce the need for maintenance. Two hand-tight connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The ADT914 is an ideal comparison test pump for pressure instruments calibration.

Generate 95% vacuum to 375 psi (25 bar) pressure



- · Portable, only 3.3 lb
- · Great stability and high resolution
- Minimal maintenance · Hand-tight connectors

SPECIFICATIONS

- Media: Air.
- Generated Pressure Range
- 14 psi (0.95 bar) vacuum to 375 psi (25 bar) positive pressure
- Pressure Resolution: 10 Pa (0.1 mbar).
- Material

Ram/adapters: SST Body: SST/aluminum

Seals: Buna-N

■ Connection

Hand-tight connectors for both test gauge and reference gauge. Test Gauge Connection: 1/4" NPT female. Reference Gauge Connection: 1/4" NPT female.

■ Dimensions

Height: 5.12" (130 mm)

Base: 9.45" (240 mm) x 4.72" (120 mm)

■ Weight

3.31 lb (1.5 kg).

FEATURES

■ Portable Only 3.3 lb

■ High Resolution

10 Pa (0.1 mbar)

High-quality screw press for fine pressure adjustment

■ Great Stability

A specially designed shut-off valve makes the pressure as stable as possible during calibration

■ Durable and Minimal Maintenance

Built-in gas-liquid isolator protects the pump from moisture and dirt


■ Easy-to-use

■ Hand-tight Connectors

Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches

ORDERING INFORMATION

■ Model Number



ntional Assessari

Model number	Description
ADT 103	Adapter and fittings, 1/4" NPT male to various male and female connections.
9901-914	Carrying Case for one ADT914 pump and two ADT681 gauges or ADT672 calibrators
ADT100-HTK-2	Hose Test Kit, 5 feet flexible hose, 8000 psi, 1/4NPT male to 1/2NPT female hand-tight quick connector.
ADT100-HTK-4	Hose Test Kit, 5 feet flexible hose, 8000 psi, 1/4NPT male to 1/4NPT female hand-tight quick connector.
ADT100-HTK-8	Hose Test Kit, 5 feet flexible hose, 8000 psi, 1/4NP1 male to 1/8NPT female hand-tight quick connector.
ADT100-HTK-B	Hose Test Kit, 5 feet flexible hose, 8000 psi, 1/4NP1 male to 1/8NPT female hand-tight quick connector.